

Protect and Serve



VS-C

The VS-C Series : perfection for your personal and small office computers.
Protects systems against :

★ Blackouts ★ Sags ★ Surges

Smallest and lightest in its class this high frequency and high efficiency UPS provides complete protection for a workstation and its peripherals.



Features :

- * 3 UPS outlets + 3 surge protected outlets
- * Integrated protection for telephone / modem / LAN card
- * Cold start capability
- * 1050 Joules surge energy rating
- * Auto restart & self-diagnostics
- * RS232 communication port
- * Easy battery replacement
- * 4 hours recharge time
- * 0.6 power factor compared to 0.5 by other producers

Faster
Recharge
Time

+

Higher
Power
Factor

=


Better
Protection

BACK UP TIME (TYPICAL)

VS375C	1PC+1LCD	8 mins
VS575C	1PC+1LCD	11 mins



▶ FRONT PANEL



- A) ON / OFF, TEST / SILENCE
- B) AC Mode
- C) Battery Mode
- D) Battery Fault



110V

220V

VS-C



Model Name	VS375C	VS575C
Topology	Standby	
On-battery Output Waveform	Step Wave	
INPUT		
Maximum Capacity	375VA / 225W	575VA / 345W
Nominal Input Voltage	100 / 110 / 120Vac or 220 / 230 / 240Vac	
Nominal Input Frequency	50Hz / 60Hz Auto Sensing	
Input Voltage Range	Rated Voltage +/- 20%	
Input Short Protection	Circuit Breaker (US), Fuse (IEC)	
OUTPUT		
Nominal Output Voltage	100 / 110 / 120Vac or 220 / 230 / 240Vac	
Output Voltage Regulation	Rated Voltage +/- 5%	
Transfer Time	4 ms (typical)	
Number of Outlets	3 Battery backup + 3 Surge (US) 3 Battery backup + 3 Surge (IEC)	
PROTECTION		
Data Line Surge Protection	RJ11 / RJ45	
Surge Energy Rating	1050 Joules	
Normal Mode Noise Suppression	Full time EMI/RFI filtering	
BATTERY		
User Replaceable Battery	12V/3AH x 1	12V/3.5AH x 1
Recharge Time to 90%	< 4 Hours	
COMMUNICATIONS INTERFACE		
Communication Port*	RS232	
ENVIRONMENTAL		
Operation Temperature	0°~40°C / 32°~104°F	
Storage Temperature	-20°~60°C / -4°~140°F	
Audible Noise	<40dBA	
PHYSICAL		
Dimensions (Physical / Packing)	7.9 x 3 x 6.9 / 9.6 x 5 x 9.8	
(L x W x H)	(mm) 200 x 77 x 175 / 245 x 128 x 250	
Weight (Net / Gross)	5.1 / 6.5	5.1 / 6.6
	(lbs)	(kg)
	2.3 / 2.9	2.4 / 3
CONFORMANCE		
Approvals	BSMI ; CE UL / cUL ; C-Tick , A-Tick ; GOST-R	

Specifications are subject to change without notice.

* You can purchase RS232 to USB cable.



OPTI-UPS Asia
Tel: +886-2-2246-7272
Fax: +886-2-2246-7312
Toll Free: 0800-029898
info@opti-ups.com.tw
http://www.opti-ups.com.tw

OPTI-UPS USA
Tel: +1-909-869-5700
Fax: +1-909-869-5730
Toll Free: (888) OPTI-UPS
info@opti-ups.com
http://www.opti-ups.com

OPTI-UPS Europe
Tel: +49-89-37-156-42-0
Fax: +49-89-37-156-42-29
info@opti-ups.de
http://www.opti-ups.de

OPTI-UPS Australia
Tel: +61-3-9545-5322
Fax: +61-3-9545-5669
Toll Free AU: 1800-678-428
Toll Free NZ: 088-OPTI-UPS
info@optiups.com.au
http://www.optiups.com.au

OPTI-UPS Czech
Tel: +420-604-444077
Fax: +420-604-444077
info@opti-ups.cz
http://www.opti-ups.cz